

Cylindrical LTO Battery Cells

Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions		Rate (C)	Approx Weight (g)
			Diameter (mm)	Height (mm)		
EJLTO1865	2.4	1100	18.5	65	10	37.5
EJLTO1865	2.4	1300	18.5	65	10	38.5
EJLTO1450	2.4	500	14	50	20	16.6
EJLTO1335	2.4	250	13	35	20	9.5
EJLTO1030	2.4	100	10	30	30	4.7
EJLTO1020	2.4	50	10	20	30	3.05
EJLTO1015	2.4	40	10	15	30	2.4
EJLTO1010	2.4	20	10	10	30	1.6
EJLTO7212	2.4	8	7.2	12	30	0.85
EJLTO0408	2.4	1.8	4	7	30	0.22
EJLTO1045	1.8	150	10	45	30	6.8
EJLTO55345F	1.8	45000	55	345	5	1800
EJLTO38345	2.4	15000	38	345	3	1000
EJLTO38345	2.4	20000	38	345	3	1000
EJLTO55235	2.4	30000	55	235	3	1200
EJLTO55345	2.4	45000	55	345	3	1850
EJLTO55345	2.4	55000	55	345	3	1950

Prismatic LTO Battery Cells

Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions(mm) (L*W*T)	Rate (C)	Approx Weight (g)
EJLTO127108210	2.4	20000	210*108*12.7	10	713
EJLTO326115170	2.4	26000	170*115*32.6	10	960
EJLTO52173139	2.4	75000	139*173*52	2	2350