



| Model No. | Configuration | Voltage | Capacity | Nominal Rate | Charger Voltage Limit | Charger Current Limit | Approx Weight |
|-------------|----------------------------|---------|----------|--------------|-----------------------|-----------------------|---------------|
| EJOT24V-06A | Panasonic CGR18650CG -7S4P | 24V | 9.0Ah | 216Wh | 42V | 3A | 2.80Kg |
| EJOT24V-06B | Panasonic NCR18650-7S4P | 24V | 11.6Ah | 278Wh | 42V | 3A | 2.80Kg |
| EJOT24V-06C | Samsung ICR18650-22F-7S4P | 24V | 8.8Ah | 211Wh | 42V | 3A | 2.80Kg |
| EJOT24V-06D | Samsung ICR18650-26F -7S4P | 24V | 10.4Ah | 250Wh | 42V | 3A | 2.80Kg |
| EJOT24V-06E | Panasonic CGR18650CH -7S4P | 24V | 8.8Ah | 211Wh | 42V | 5A | 2.80Kg |
| EJOT24V-06F | Samsung ICR18650-22P -7S4P | 24V | 8.4Ah | 201Wh | 42V | 5A | 2.80Kg |

● **Cycle Life**

Standard charge mode, keep for 30min;Standard discharge mode:>500cycle,70%

● **Standard Charge Model**

Charge to 42V with constant current ,then charge with constant voltage till current less than 300mA.
Use special charger:CC+CV,2A,42V/300mA

● **Options**

Standard BMS: overcharge protection, overdischarge protection ,overcurrent protection balance&high temperature protection

Smart BMS,Standard BMS functions,scale,communication,sleep,encode,tailights blinking,5V USB output

● **Certificate**

FCC,CE,MSDS