



| Model No.   | Configuration               | Voltage | Capacity | Nominal Rate | Charger Voltage Limit | Charger C urrent Limit | Approx Weight |
|-------------|-----------------------------|---------|----------|--------------|-----------------------|------------------------|---------------|
| EJBO36V-01A | Panasonic CGR18650CG -10S3P | 36V     | 9.0Ah    | 324Wh        | 42V                   | 3A                     | 2.80Kg        |
| EJBO36V-01B | Panasonic NCR18650-10S3P    | 36V     | 11.6Ah   | 417Wh        | 42V                   | 3A                     | 2.80Kg        |
| EJBO36V-01C | Samsung ICR18650-22F-10S3P  | 36V     | 8.8Ah    | 316 Wh       | 42V                   | 3A                     | 2.80Kg        |
| EJBO36V-01D | Samsung ICR18650-26F -10S3P | 36V     | 10.4Ah   | 374 Wh       | 42V                   | 3A                     | 2.80Kg        |
| EJBO36V-01E | Panasonic CGR18650CH -10S3P | 36V     | 8.8Ah    | 316Wh        | 42V                   | 5A                     | 2.80Kg        |
| EJBO36V-01F | Samsung ICR18650-22P -10S3P | 36V     | 8.4Ah    | 302 Wh       | 42V                   | 5A                     | 2.80Kg        |

### ● Cycle Life

Standard charge mode, keep for 30min;Standard discharge mode:>500cycle,70%

### ● Standard Charge Model

Charge to 42V with constant current ,then charge with constant voltage till current less than 300mA.

Use special charger:CC+CV,2A,42V/300mA

### ● Options

Standard BMS: overcharge protection, overdischarge protection ,overcurrent protection balance&high temperature protection

Smart BMS,Standard BMS functions,scale,communication,sleep,encode,taillights blinking,5V USB output

### ● Certificate

FCC,CE,MSDS



Manufacturer reserves the right to alter or amend the approval sheet without the prior notice